



**L1406M**  
**REFLECTIONS RECEPTACLE**  
32-gallon plastisol coated, slotted steel receptacle with galvanized spun steel top and black plastic liner

**Replacement Parts**

Universal Contour Top **F3005**

Black Plastic Liner **F1017**

**Accessories**



Traditional Inground Mount **F1094**

Traditional Surface Mount **F1098**

45° Surface Mount **F1406**

45° Inground Mount **F1407**

Corkscrew Anchor **A1020**



**Shipping Information**

Unit Wt.	Unit Shipping Wt. UPS (1 unit)	Unit Shipping Wt. Truck (2+ units)	Unit Ship Size w/Pallet	Max Units per Pallet	Pallet Wt. (48" x 48")	Total No. Pkgs	Shipping Class
72 lbs	100 lbs/unit	80 lbs/unit	32 cu. ft.	8	50 lbs	1	100

**Material**

The 32-gallon receptacle body is made of 12-gauge slotted steel with a .44" wide gap uniform pattern. A spun steel contour top and plastic liner is included. The receptacle is protected by Fusion Advantage™, a plastisol coating with an average .125" thickness and a high-gloss powder coat.

The contour top is made of 18-gauge galvanized steel protected with a high-gloss powder coat finish. The top features a 10-inch diameter center opening for easy waste disposal and includes a 14-inch web security strap.

The reusable 32-gallon plastic liner is made of black high-density polyethylene.

**Options and Accessories**

Optional mounting kits for various applications are available.

**Finish**

Fusion Advantage is a heat fused plastisol coating that creates an impervious rustproof barrier and resists UV deterioration, mildew, staining and fading.

The finish has been tested to the requirements of ASTM E1354 and is determined to be in compliance with California Uniform Fire Code 1103.2.1.4.2.

**Color**

See website or sales representative for color choices.

**Assembly**

No assembly is required. Purchase of mounting options may require additional minor assembly.

**Maintenance**

The product is virtually maintenance-free and requires only periodic cleaning with a sponge and a solution of mild detergent and water to remove surface dirt. Do not clean with solvent or petroleum based products.